



Lutron PH-201 DIGITAL PH/mV/TEMP METER

- **Economical cost** digital PH meter
- **General purpose** applications
- **Easy operation**
- **Compact size**, light weight
- **Applications:** water conditioning, aquariums, beverage, fish hatcheries, food processing, photography, laboratory, paper industry, school and colleges, plating industry, quality control, swimming pools
- **Supplied without** PH electrode

OPTIONAL ACCESSORIES	
HS-02	Carrying case
CA-04	Carrying soft case
PE-01	PH electrode (0-14 PH)
PE-11	PH electrode (0-14 pH)
PE-03	PH electrode (0-13 pH)
PH-04	Calibration solution (pH 4)
PH-07	Calibration solution (pH 7)

SPECIFICATIONS	
Display:	13 mm LCD, 3 1/2 digits
Measurement:	PH
Range/resolution:	0 to 14 pH x 0.01 pH
Accuracy:	PH5 - PH9 ±0.07 pH
	PH4 - PH10 ±0.1 pH
	PH1 - PH3.9 - PH10.1 - PH13 ±0.2 pH
Input impedance:	10-12 ohms
PH range temp. compensation:	no adjust.
Sampling time:	approx. 0.4 second
Operating temperature:	0°C to 50°C (32°F to 122°F)
Operating humidity:	less than 80% RH
Calibration knob:	external PH 4 (slope adj.) & PH 7 (cal.adj)
Power supply:	006P DC 9V battery
Power consumption:	approx. 2.0 mA
Dimension:	131 x 70 x 25 mm
Weight:	153 gr. (including battery)