

TES 1319A Thermometer



Features:

- ✓ Type "K" Thermocouple Input.
- ✓ Switchable Resolution 0.1° / 1 °
- ✓ With °C & °F switching.
- ✓ Max / MIN Function.
- ✓ Data Hold Function.
- ✓ Flip-up stand.

Specification:

Measuring Rang	- 50 °C ~ 1350°C , -58 °F ~ 1999 °F
Sensor	K Type Thermocouple
Input	Single Channe
Resolution	- 50 °C ~ 199.9 °C.....0.1 °C , - 50 °F ~ 199.9 °F.....0.1 °F (Others 1 °C/1 °F)
Accuracy	- 50 °C ~ 199.9 °C... +/- (0.3%rdg + 1 °C) - 50 °F ~ 199.9 °F... +/- (0.3%rdg + 2 °F) - 50 °C ~ 1000 °C... +/- (0.5%rdg + 1 °C) - 50 °F ~ 1999 °F... +/- (0.5%rdg + 2 °F) 1001 °C ~ 1300 °C... +/- (0.75%rdg + 1 °C)
Temperature Coefficient	Less than 0.1 times the applicable accuracy specification per °C (°F)
Sampling Rate	2.5 times / sec
Operating / Storage Conditions	0 °C ~ 40 °C<80%RH , - 10 °C ~ 60 °C< 70%RH
Power Source	6 pcs AAA size Battery